



LONG TERM STORMWATER MANAGEMENT INSPECTION REPORT

Site Name: _____

Inspector: _____

Date: _____

POLLUTION EVIDENCE:

SUGGESTED MAINTENANCE:

REQUIRED MAINTENANCE:

For required maintenance items, Lehi City will return and reinspect every 7 to 10 days until all items are resolved to the satisfaction of the inspector. If the owner has taken no action to resolve the required maintenance items within 30 days of the first inspection, Lehi City will perform the required maintenance and bill the owner for the expense. (Lehi City Code 9-3-5 C. 2.)



METHODS OF REDUCING STORMWATER POLLUTION

ELIMINATING ILLICIT DISCHARGES

An Illicit Discharge is the discharge of anything other than clean, clear water into the storm drain system. Storm drains empty directly to the nearest local water body without any treatment. That means anything that goes down a storm drain eventually ends up in Spring Creek, Utah Lake, or the Jordan River. Illicit Discharges are prohibited in Lehi City and there are fines and civil penalties imposed for knowing violations.

POLLUTION PREVENTION IN DAY-TO-DAY OPERATIONS

Lawn Maintenance:

- Apply fertilizer and pesticides sparingly and don't fertilize before a rainstorm.
- Sweep or blow excess grass clippings and fertilizer back onto laws.
- Adjust sprinklers so they don't water paved surfaces.

Salt and Deicing Materials:

- Apply salt and deicing materials sparingly.
- Store salt and deicing materials in covered, leak proof containers.

Dumpsters and Trash:

- Keep dumpster and trash receptacle lids closed to prevent blowing trash and leaking caused by precipitation.
- Replace leaking dumpsters.
- Know and follow your disposal facility requirements and regulations.

Parking Lot Maintenance:

- Whenever possible, sweep parking lots rather than wash them.
- When washing pavements, prevent all wash water from entering the storm drain by directing it into landscaping or vacuuming it up.
- Clean up spills using absorbent material such as floor dry, cat litter, or dirt. Sweep up and dispose properly.

Chemical and Material Storage:

- Store liquids in covered, leakproof containers.
- Do not store erodible materials on paved surfaces.

Building and Equipment Maintenance:

- Dispose of all mop water and other wash waters down the sanitary sewer, not the storm drain.
- Never work on vehicles in the street or near a storm drain or drainage ditch.
- Place a tarp, ground cloth, sheet of plywood, cardboard, or newspaper under leaking vehicles to absorb spills.

Benefits of Onsite Infiltration of Storm Water

- Directing runoff from roofs and parking lots into landscaped areas can reduce irrigation costs.